



**COFAIR
PRODUCTS, INC.**

Box 2715, 4236 Commerical Way, Glenview, IL 60025 • 847-375-9390 • Fax: 847-375-9394 • www.cofair.com

PRODUCT INFORMATION SHEET

MATERIAL SAFETY DATA SHEET

Co-Fair Corporation
PO Box 2715
4236 Commercial Way
Glenview, IL 60025
(847) 375-9390

Dated: March 28, 1986
Revised: January 1, 2002

SECTION 1 - PRODUCT INFORMATION

Trade name: **Gutter Seal/Gutter Liner**

Description: Waterproofing membrane based on polymer-modified asphalt.

HMIS Hazard Rating (0 = least 1 = slight 2 = moderate
3 = high 4 = extreme)

Health - 1

Flammability - 1

Reactivity - 0

SECTION 2 - HAZARDOUS INGREDIENTS

<u>Ingredient</u>	<u>C.A.S. Number</u>	<u>Exposure Limit</u>
Asphalt fume	8052-42-4	OSHA PEL ACGIH TLV None 5 mg/M3

Carcinogenicity: Asphalt is IARC listed

SECTION 3 - PHYSICAL DATA

Boiling Point:	Not Applicable
Solubility in Water:	Nil
Appearance and odor:	Black resinous material
Specific Gravity (H2O = 1.0):	0.9
Melting Point:	>200 degrees Fahrenheit

SECTION 4 - FIRE AND EXPLOSION HAZARD DATA

Flash Point:	>400 degrees Fahrenheit
Method Used:	Cleveland Open Cup
Extinguishing Media:	Dry chemical or foam
Special Fire Fighting Instructions:	Treat as hydrocarbon fire

SECTION 5 - HEALTH HAZARD DATA

Primary Route of Entry:

Inhalation, skin

Health Hazards:

No data

Acute

Upper respiratory tract irritation. May cause nausea or dizziness.

Chronic

There are no studies to indicate that asphalt causes cancer in man. This petroleum based product contains a small amount of polyaromatic hydrocarbons which have been shown to cause cancer and respiratory damage in laboratory animals

Skin Contact

Acute

Prolonged exposure to cold material may cause dermatitis. Contact with hot material will cause thermal burns. Exposure to asphalt fumes increase sensitivity to sunburn.

Chronic

Mouse skin painting studies give evidence of skin cancer.

Eye Contact

Acute

Fumes from heated material will cause irritation.

Chronic

None known

Signs and Symptoms of Exposure

Upper respiratory tract, eye and skin irritation.

EMERGENCY FIRST AID PROCEDURES

Inhalation

Remove individual to fresh air. If irritation persists, administer oxygen and seek medical attention.

Skin

Cool hot material with ice or cold water. DO NOT REMOVE ASPHALT IMMEDIATELY. Cover with petroleum jelly and remove when softened. Seek medical attention.

Eyes

Flush with running water for at least 15 minutes. Seek medical attention.

Ingestion

Do NOT induce vomiting. In general, no treatment is necessary unless large quantities of product are ingested. However, get medical advice.

SECTION 6 - REACTIVITY DATA

Stability

Stable

Conditions to avoid

None that are known

Hazardous Decomposition Products

CO, CO₂ and various hydrocarbons.

Hazardous Polymerization

Will not occur

SECTION 7 - SPILL OR LEAK PROCEDURES**Action to take for spills**

Material is solid

Waste Disposal Method

Approved for landfills

SECTION 8 - SPECIAL PROTECTION INFORMATION

This section applies when working with material heated above ambient temperature.

Ventilation

Ambient or natural, mechanical ventilation may be needed when working in confined spaces.

Respiratory Protection

If fumes exceed 5-mg/M³ uses approved organic vapor respirator with a particulate prefilter.

Protective Clothing

Long sleeve shirt, long pants and gloves should be worn when working with hot material.

Eye Protection

Safety glasses or face shield.

Work/ Hygienic Practices

Work upwind from asphalt fumes. Wash with soap and warm water at end of day.